

# DL07 DRILL

# STANLEY®



## FEATURES:

- Instant reverse for high reliability and efficiency in all types of drilling applications.
- Dual-position Assist Handle on some models provides increased control and performance on tough drilling jobs.
- The new over-sized reversing spool is protected by heavy-duty wiper seals. These wiper seals clean away dirt as the spool is moved.
- Ideal for drilling holes in wood, metal and masonry

**DL07 DRILL IS IDEAL FOR  
DRILLING HOLES IN WOOD,  
METAL AND MASONRY -  
THE POWER OF  
HYDRAULICS**

## SPECIFICATIONS

### DL07

Capacity	1/2 in. Chuck
	12 mm Chuck
Weight*	6 lb
	2.7 kg
Length*	9 in.
	22.90 cm
Ports	-8 SAE O-Ring
Motor	Stanley Hyrevz™ Gear
System Type	Open Center/Closed Center
Maximum Flow	12 gpm
	45 lpm

### Torque

U.S.A	Metric
4 ft lb @ 500 psi	.5 Nm @ 35 bar
9 ft lb @ 1000 psi	1.2 Nm @ 70 bar
14 ft lb @ 1500 psi	1.9 Nm @ 105 bar
19 ft lb @ 2000 psi	2.6 Nm @ 140 bar

### DRILL SPEED/HYDRAULIC FLOW

350 rpm @ 3 gpm	11.3 lpm
475 rpm @ 4 gpm	15 lpm
750 rpm @ 6 gpm	23 lpm
1000 rpm @ 8 gpm	70-140 bar
1250 rpm @ 10 gpm	7-9 gpm



# DL07 DRILL

**STANLEY**®

## ORDERING INFORMATION

MODEL	PART NO.	DESCRIPTION
DL07	DL07550	OC/CC*, Dual Spool, Trigger Guard, Assist Handle, 1/2 in. Chuck, Couplers, No Hose Whips
	DL0755001	OC/CC*, Dual Spool, Trigger Guard, Assist Handle, 1/2 in. Chuck, Couplers, No Hose Whips, CE
	DL07652	OC/CC*, Dual Spool, Trigger Guard, 1/2 in. Chuck, Assist Handle, Hose Whips, No Couplers, Underwater Use

## ACCESSORIES

ITEM NO.	DESCRIPTION	ITEM NO.	DESCRIPTION
Carbide Tipped Augers with 7/16 in. Shank		Carbide Tipped Augers with 7/16 in. Shank	
27850	9/16 in. Dia., 8 in. Twist, 12 in. OAL	27861	11/16 in. Dia., 18 in. Twist, 22 in. OAL
27851	11/16 in. Dia., 8 in. Twist, 12 in. OAL	27862	13/16 in. Dia., 18 in. Twist, 22 in. OAL
27852	13/16 in. Dia., 8 in. Twist, 12 in. OAL	27863	15/16 in. Dia., 18 in. Twist, 22 in. OAL
27855	9/16 in. Dia., 12 in. Twist, 16 in. OAL	27864	1-1/16 in. Dia., 18 in. Twist, 22 in. OAL
27856	11/16 in. Dia., 12 in. Twist, 16 in. OAL	27865	11/16 in. Dia., 32 in. Twist, 36 in. OAL
27857	13/16 in. Dia., 12 in. Twist, 16 in. OAL	27869	13/16 in. Dia., 36 in. Twist, 48 in. OAL
27858	15/16 in. Dia., 12 in. Twist, 16 in. OAL	32400	13/16 in. Dia., 15 in. Twist, 18 in. OAL
27859	1-1/16 in. Dia., 12 in. Twist, 16 in. OAL	OAL = Over All Length	
27860	9/16 in. Dia., 18 in. Twist, 22 in. OAL		

### WARRANTY:

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

**STANLEY**®Stanley Hydraulic Tools | 3810 SE Naef Road | Milwaukie, Oregon 97267 | +01.503.659.5660 | 800.972.2647 | [www.stanleyhydraulic.com](http://www.stanleyhydraulic.com)