

HD25 Hammer Drill Data Sheet

0121 506 6095 or enquiries@echopkins-bham.co.uk



SPECIFICATIONS		
DRILLING CAPACITY	Up to 25mm	
BLOWS PER MINUTE	4,460 bpm	
HYD FLOW RANGE	15 to 50 Litres per minute	
MAXIMUM FLOW	50 Litres per minute	
PRESSURE	80 Bar (integrated PRV)	
PORTS	-8 SAE O-Ring	
WEIGHT	8.2 Kg	
LENGTH	475 mm	
CONNECTION	3/8 Body Flat Face Couplers	
HYD MOTOR	0.60 kw / 625 rpm @ 50 lpm	
HYD SYSTEM TYPE	Open Centre	
CHUCK TYPE	SDS-Plus	

Features and Benefits

The versatile HD25 hydraulic driven hammer drill is ideal for just about any drilling job.

Its powerful pneumatic hammer function makes it easier to drill into rock, concrete, masonry and other such materials, but the hammer function can be turned off for efficient light drilling in materials such as wood and metal. Simply install the adaptor and chuck, then use standard wood auger bits or twist drills.

This professional tool features a D-handle and large multipositional assist handle which makes it easier to manoeuvre than a pistol drill. The power-toweight ratio of the HD25 brings even the toughest jobs down to

size. The Hammer Drill also comes complete with a depth gauge attachment.

The HD25 now comes with a builtin pressure relief valve protecting the tool to its rated 80bar.

This tool is primarily for underwater use but can also be used on land.



HD25 - 11/2020 v6

Visit our website at www.echopkins.com

E.C. Hopkins Limited Woodgate Business Park Birmingham B32 3DB

Tel: +44 (0)121 506 6095

e-mail enquiries@echopkins-bham.co.uk



HD25 Hammer Drill Data Sheet

0121 506 6095 or enquiries@echopkins-bham.co.uk

ORDERING INFORMATION

MODEL/PART No. DESCRIPTION

Hydraulic driven Hammer Drill, Underwater Model
HD25UW-PRV OC, Integrated Pressure Relief Valve, Assist Handle,
SDS-Plus Chuck, Depth Gauge, Couplings

WARRANTY

Spitznas tools and accessories are all subject to the manufacturer warranty. This warranty becomes void if maximum flow and pressure ratings are exceeded.

ACCESSORIES		
PART No.	DESCRIPTION	
547600	Adaptor SDS-Plus x 1/2-20 thread (Used with P/No. 6287D)	
6287D	Drill Chuck 13mm Capacity (Requires P/No. 547600)	
531077108	Adaptor SDS-Plus x 1/2" BSP Female (Wet Core Drill Bits)	
522975401	Adaptor SDS-Plus x 1/2" BSP Male (Dry Core Drill Bits)	

PART No. DESCRIPTION 2.2406.001T Seal Kit 2.2406.001R Repair Kit 04337 O-Ring Tool Kit

TEST EQUIPMENT		
04182	Flow & Pressure Tester	

All Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult us.

HD25 - 11/2020 v6

Visit our website at www.echopkins.com

E.C. Hopkins Limited Woodgate Business Park Birmingham B32 3DB

Tel: +44 (0)121 506 6095

e-mail enquiries@echopkins-bham.co.uk