



### SPECIFICATIONS

|                      |                             |
|----------------------|-----------------------------|
| Output Capacity      | 20 ~ 30 LPM (EHTMA CAT C~D) |
| Full Pressure Relief | 155 Bar (2250 Psi)          |
| Circuit Type         | Open Centre                 |
| Connectors / Size    | See ordering information    |
| Hydraulic Capacity   | 11.4 Litres                 |
| Fuel Tank Capacity   | 20.8 Litres                 |
| Engine Oil Capacity  | 1.4 Litres                  |
| Engine Type          | B&S 18 HP Vanguard OHV      |
| Starting System      | 12v Battery Start           |
| Fuel Type            | Unleaded Petrol             |
| Weight               | 150 Kg (Wet)                |
| Dimensions           | L 89 x W 55 x H 74cm        |

### Features and Benefits

The Stanley HP8 hydraulic power unit is designed for continuous duty operation of any hydraulic tool in the EHTMA category of C and D. The HP8 provides world class cooling in a compact powerful unit.

- EHTMA Category C and D hydraulic circuit with superior cooling.
- Tool circuit lockout during start up – safety feature.
- Lift & Latch handle with fold-up side handles
- Quartz hour meter on control panel records engine run time.
- 35-AH sealed, non-spillable, no maintenance battery located in covered compartment.
- In tank hydraulic filter with dipstick and easy access filter replacement.

**STANLEY®**

### ORDERING INFORMATION

#### MODEL/PART No. DESCRIPTION

|          |  |
|----------|--|
| HP8BA    | Hydraulic Power Pack<br>20 ~ 30 LPM @ 155 BAR<br>B&S 18 HP Vanguard OHV<br>12v Battery Start<br>1/2" Flat Face Hyd Couplers<br>7.5m Hydraulic Hose set |
| HP8BA-34 | Hydraulic Power Pack<br>20 ~ 30 LPM @ 155 BAR<br>B&S 18 HP Vanguard OHV<br>12v Battery Start<br>3/4" Flat Face Hyd Couplers                            |

### WARRANTY

Hydraulic Tools, Power Units and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. EC Hopkins reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

### ACCESSORIES

| PART No.        | DESCRIPTION  | TO SUIT  |
|-----------------|--|----------|
| HS07M08B3-FF    | Hyd Hose Set 7m, 1/2" FF Couplers, ISO32 Oil         | HP8BA    |
| HS10M10B3-FF    | Hyd Hose Set 10m, 1/2" FF Couplers, ISO32 Oil        | HP8BA    |
| HS15M10B3-FF    | Hyd Hose Set 15m, 1/2" FF Couplers, ISO32 Oil        | HP8BA    |
| HS20M10B3-FF    | Hyd Hose Set 20m, 1/2" FF Couplers, ISO32 Oil        | HP8BA    |
| HS30M10B3-FF    | Hyd Hose Set 30m, 1/2" FF Couplers, ISO32 Oil        | HP8BA    |
| HS020M1012B2-FF | Hyd Hose Set 20m, 1/2" & 3/4" FF Couplers, ISO32 Oil | HP8BA-34 |
| HS030M1012B2-FF | Hyd Hose Set 30m, 1/2" & 3/4" FF Couplers, ISO32 Oil | HP8BA-34 |
| HS040M1012B2-FF | Hyd Hose Set 40m, 1/2" & 3/4" FF Couplers, ISO32 Oil | HP8BA-34 |
| HS050M1012B2-FF | Hyd Hose Set 50m, 1/2" & 3/4" FF Couplers, ISO32 Oil | HP8BA-34 |

### SERVICE ITEMS / TOOLS

| PART No. | DESCRIPTION |
|----------|-------------|
| SK1-GT18 | Service Kit |

### TEST EQUIPMENT

|       |                        |
|-------|------------------------|
| 04182 | Flow & Pressure Tester |
|-------|------------------------|



All E.C. Hopkins tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult E.C. Hopkins Limited.