



## Husqvarna DM 230

*New, handheld drill motor with attractive design and functional ergonomics. Soft rear section and a larger contact area mean that it sits better against your body. The machine is modular, and therefore easy to maintain and repair.*



### **HANDLE WITH INTEGRATED WATER HOSE**

The handle has an integrated water hose, which together with the electric cable run parallel conveniently from the machine.



### **SMART START®**

By pressing the SmartStart button speed is reduced by half, which facilitate to start drilling.



### **SOFT REAR SECTION**

The DM 230 sits comfortable against your body due to the soft rear section and a larger contact area.



### **THREE GEARS**

The DM 230 is equipped with three gears.

## Features Husqvarna DM 230

- If the motor runs at too high a load for a long period, it will start to pulsate. If the load is not reduced the motor will shut off, to prevent overheating. Elgard™ significantly increases the machine's service life.
- Functional ergonomics make the Husqvarna drill motors easy and convenient to operate.
- An electronic current limiter for softer starts. Full speed is reached about two seconds after the switch is turned on.
- Equipped with Elgard™ which uses pulsation to indicate when the machine is overloaded. This extends product life.
- When making a starter hole or cutting through reinforcement speed can be reduced by half using SmartStart.
- SoftStart™ – electronic current limiter means full speed is reached about two seconds after start.
- Three-speed water-cooled gearbox for optimal drilling performance and longer service intervals.
- The plastic housing makes it more durable against drops and daily wear.

TECHNICAL SPECIFICATION	
Voltage	230/110V
Amperage	8/15 A
Power	1850 W
Output RPM	700/1700/3600 rpm
Output RPM at full load	500/1400/2900 rpm
Power rating	1100 W
Speeds	3
Water coupling	G 1/4"
Rated output, W	1100/0 W
Rated current, A	8/15 A
Spindle speed idle high speed	900/2150/4500 rpm
Max drill bit diameter, handheld	75 mm / 3 inch
Max drill bit diameter, stand	150 mm / 6 inch
Mounting collar	60 mm / 2.36"
Spindle thread, outer	1 1/4" 7 UNC
Spindle thread, inner	G 1/2" or 5/8" 11 UNC
UNC water coupling	G 1/4"
Weight	7 kg / 15.4 lbs
Sound pressure	90 dB(A)
Sound level	94 dB(A)
Hand arm vibration (Aeq)	2.5 m/s <sup>2</sup>