



## Husqvarna DM 280

*This newly developed drill motor from Husqvarna is extremely easy to operate. The DM 280 features an ergonomic handle that makes it easy to carry around. The controls are designed and positioned to further enhance ergonomics and to facilitate drilling. The DM 280 can be used on all of Husqvarna's larger drill stands, and for drill bits from 50 to 350 mm in diameter. The machine has three gear stages, so you can find the optimal drilling speed.*



## Features Husqvarna DM 280

- If the motor runs at too high a load for a long period, it will start to pulsate. If the load is not reduced the motor will shut off, to prevent overheating. Elgard™ significantly increases the machine's service life.
- An electronic current limiter for softer starts. Full speed is reached about two seconds after the switch is turned on.
- Equipped with Elgard™ which indicates via the LED when the machine is overloaded. This allows the operator to always drill at maximum pressure and prevents engine damage and extends product life.
- When making a starter hole speed can be reduced by half using SmartStart.
- SoftStart™ – electronic current limiter means full speed is reached about two seconds after start.
- The machine has a designed handle for easier transport and faster set-up.
- The controls are designed and positioned to enhance ergonomics and facilitate operation.
- The water hose can turn 180°, for greater flexibility in terms of setup configuration.

| TECHNICAL SPECIFICATION            |                  |
|------------------------------------|------------------|
| Voltage                            | 230/110V         |
| Power                              | 2700 W           |
| Phases                             | 1                |
| Speeds                             | 3                |
| Spindle speed full load low speed  | 240/540/930rpm   |
| Spindle speed full load high speed | 350/780/1340rpm  |
| Rated output, W                    | 1750/1850 W      |
| Rated current, A                   | 13/25 A          |
| Spindle speed idle high speed      | 440/970/1670 rpm |
| Spindle speed idle low speed       | 300/660/1140 rpm |
| Max drill bit diameter, stand      | 350 mm / 14 inch |
| Spindle thread, outer              | 1 1/4" UNC       |
| UNC water coupling                 | G 1/4"           |
| Weight                             | 13 kg/29 lbs     |

