### **STANLEY**

# IW16 IMPACT WRENCH



- Medium to heavy duty wrench ideal for nut and bolt driving, anchor bolts and drilling applications.
- Designed to run from a wide range of hydraulic circuits, the IW16 has adjustable impact intensity making it ideal for a wide range of heavy duty driving.
- The large "D" handle and feathering trigger is convenient and gives the operator complete control of the wrench.
- Just set the direction of rotation to either tighten or loosen a fastener, squeeze the trigger for up to 2500 ft lbs (3400 Nm) of torque.
- Standard reversing valve provides instant change over from forward to reverse.



### **SPECIFICATIONS**

IW16	
Capacity	1 in. Square Drive
Torque	500 - 2500 ft lbs
	680 - 3400 Nm
Input Pressure	1500 - 2000 psi
	105 - 140 bar
Weight	26 lbs
	12 kg
Length	14.5 in.
	37 cm
Width	4.5 in.
	11 cm
Connection	3/8 in. Male Pipe Adapter
Ports	-8 SAE O-Ring
Motor	Integral
Hose Whips	No
Maximum Flow	7 - 12 gpm
	26 - 45 lpm

2500 FT. LBS OF PURE TORQUE -THE POWER OF HYDRAULICS

## STANLEY

# IW16 IMPACT WRENCH

MODEL	PART NO.	DESCRIPTION
IW16	IW16150	1 in. Square Drive
	IW1615001	1 in. Square Drive, CE
	IW16350	1 in. Square Drive, UNDER WATER
	IW1635001	1 in. Square Drive, CE, UNDER WATER

### **ACCESSORIES**

ITEM NO.	DESCRIPTION
31201	Adapter, 1 in. to 3/4 in. Drive
31203	Extension, 10 in., 1 in. Drive
33276	Socket Retainer Pin, 1 in. Square Drive Socket
33277	Socket Retainer Ring, 1 in. Square Drive Socket
SOCKETS	SEE SOCKET SPEC SHEET FOR A LIST OF ALL SOCKETS

#### **WARRANTY**:

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

