

HD32 Hammer Drill Data Sheet

0121 506 6095 or enquiries@echopkins-bham.co.uk



SPECIFICATIONS		
DRILLING CAPACITY	Up to 32mm	
BLOWS PER MINUTE	2,500 bpm	
HYD FLOW RANGE	20 to 50 Litres per minute	
MAXIMUM FLOW	50 Litres per minute	
PRESSURE	80 Bar	
PORTS	-8 SAE O-Ring	
WEIGHT	14.0 Kg	
LENGTH	495 mm	
CONNECTION	3/8 Body Flat Face Couplers	
HYD MOTOR	1.3 kw / 625 rpm @ 50 lpm	
HYD SYSTEM TYPE	Open Centre	
CHUCK TYPE	SDS-Max	

Features and Benefits

The versatile HD32 hydraulic driven hammer drill is ideal for just about any drilling job whether in rock, concrete or masonry.

Its powerful pneumatic hammer function makes it easier to drill into rock, concrete, masonry and other such materials, but the hammer function can be turned off for efficient light drilling in materials such as wood and metal.

This professional tool features a D-handle and large multipositional assist handle which makes it easier to manoeuvre than a pistol drill. And, the power-to-weight ratio of the HD32 brings even the toughest jobs down to size.

The HD32 also comes complete with a depth gauge attachment.

This tool is primarily designed for underwater use but can also be used on land.



HD32 - 11/2020

Visit our website at www.echopkins.com

E.C. Hopkins Limited Woodgate Business Park Birmingham B32 3DB

Tel: +44 (0)121 506 6095

e-mail enquiries@echopkins-bham.co.uk



HD32 Hammer Drill Data Sheet

0121 506 6095 or enquiries@echopkins-bham.co.uk

ORDERING INFORMATION

MODEL/PART No. DESCRIPTION

	Hydraulic driven Hammer Drill, Underwater Model
HD32UW	OC, Trigger Guard, Safety Trigger Lock, Assist Handle,
	SDS-Max Chuck, Depth Gauge, Couplings

ACCESSORIES

PART No.	DESCRIPTION
PRCM30-90	In-Line Flow Regulator & Pressure Relief Valve Assy 30lpm / 90bar

We offer a full range of SDS-Max TC Drill Bits from 12mm to 32mm Diameter in various lengths

WARRANTY

Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

SERVICE ITEMS / TOOLS

PART No.	DESCRIPTION
2.2418.001T	Seal Kit
2.2418.001R	Repair Kit
04337	O-Ring Tool Kit

TEST EQUIPMENT

04182 Flow & Pressure Tester

All Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult us.