



SPECIFICATIONS

Output Capacity	18 LPM
Full Pressure Relief	110 Bar (1600 PSI)
Circuit Type	Open Centre
Connectors / Size	½" Flat Face Hyd Couplings
Hydraulic Capacity	7 Litres
Fuel Tank Capacity	3.1 Litres
Engine Oil Capacity	1.1 Litres
Engine Type	Honda 6hp
Starting System	Recoil
Fuel Type	Unleaded Petrol
Weight	58Kg (Dry)
Dimensions (mm)	L 647 x W 490 x H 598

Features and Benefits

The Hycon HPP06 hydraulic power unit is a compact, petrol-driven solution built for professionals who need reliable hydraulic power wherever the job takes them. Powered by a robust Honda engine, it delivers dependable performance with easy starting and the flexibility to operate in remote locations. Its compact, lightweight, portable design makes it simple to transport and position on site, helping crews save time, reduce manual effort, and get to work quickly even in confined or hard-to-reach areas.

Despite its small size, the HPP06 delivers strong and consistent hydraulic output, making it ideal for running a wide range of tools such as breakers, cut-off saws, and drills. The unit's simple, open-centre hydraulic system ensures low maintenance requirements and high reliability, even in demanding environments. Combined with its durable construction and efficient cooling, this means less downtime, longer service life, and a power unit that keeps productivity high while keeping operating costs under control.

- Fitted with a safety pressure relief valve to avoid high pressure.
- 2-handle system with wheels for easy manoeuvrability.
- Very efficient air cooling which protects the unit against super-heating.
- Oil alert system for engine oil level protection.



ORDERING INFORMATION

MODEL/PART No.	DESCRIPTION
HPP06 (2020006)	18lpm @ 110 BAR Recoil Start 1/2" Flat Face Hyd Couplers

WARRANTY

Hydraulic Tools, Power Units and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. EC Hopkins reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

ACCESSORIES

PART No.	DESCRIPTION
HS07M08B3-FF	Hyd Hose Set 7m, 1/2" FF Couplers, ISO32 Oil
HS10M08B3-FF	Hyd Hose Set 10m, 1/2" FF Couplers, ISO32 Oil
HS15M08B3-FF	Hyd Hose Set 15m, 1/2" FF Couplers, ISO32 Oil

SERVICE ITEMS / TOOLS

PART No.	DESCRIPTION

TEST EQUIPMENT

4040062	Flow & Pressure Tester
---------	------------------------



All E.C. Hopkins tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult E.C. Hopkins Limited.