

KFH 17-15 R

Beveller up to 15 mm

Universal beveller with booster and spring technology for perfectly preparing welded seams.

Product number: 7 238 18 61 00 0



Details

- > Milling performance improved by 30 - 80 % and vastly reduced vibrations thanks to new booster technology.
- > Spring technology: absorption of rotational forces and therefore improved operational safety from low-vibration working.
- > FEIN ErgoGrip: unique, ergonomic concept of two-handed operation for fatigue-free working (patent pending).
- > Extensive user protection features include soft start, restart protection, jam monitoring and electronic overload protection.
- > Efficient quick-change cutter system for minimal interruptions.
- > Effective material removal requiring little force.

Price includes

- ✓ 1 tool (without milling head, without guide roller, without indexable tips)
- ✓ 1 socket head wrench 5 mm
- ✓ 6 x clamping screws
- ✓ 1 x TX 15 Torx screwdriver
- ✓ 1 x copper paste
- ✓ 1 plastic carrying case

Product feature

- ✓ Soft start
- ✓ Electronic overload protection
- ✓ Spring technology
- ✓ Restart protection
- ✓ Speed preselection
- ✓ Quick-change cutter system
- ✓ Blockage monitoring
- ✓ Booster technology

Application

Installation work



Bevel length of up to 5 mm at 45°



Bevel length of up to 8 mm at 45°



Bevel length of up to 15 mm at 45°



Workshop jobs



★ suitable
★★ well suitable

Technical data

TECHNICAL DATA

Input 1,700 W

Output 1,000 W

Speed, no load 2,300 - 7,500 rpm

Max. bevel length at 45° 15 mm

Max. bevel height at 45° 10.6 mm

Bevel angle 30° / 37.5° / 45° / 60°

Milling head configuration 3x2 KX tip

Support plate diameter 137 mm

Cable with plug 4 m

Weight according to EPTA 6.40 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA
Uncertainty of measured value
KpA 90 dB
3 dB

Sound power level LWA
Uncertainty of measured value
KWA 101 dB
3 dB

Sound peak value
LpCpeak
Uncertainty of measured value
KpCpeak 104 dB
3 dB

Vibration value 1 α_{hv} 3-way
Vibration value 2 α_{hv} 3-way α_h , 3,7 m/s²
 α_h , 4,3 m/s²

Uncertainty of measured value K α 1,5 m/s²

Application examples

