



Husqvarna TS 350 E

TS 350 E is an efficient universal masonry saw with high cutting capacity for all kinds of bricks and building blocks. With this table saw you get a maximum cutting depth of 100 mm in one pass or up to 200 mm by step cutting. You can easily plunge or bevel cut at 45 degrees for maximum versatility. The robust single-piece frame with integrated conveyor rails gives great rigidity and provides longer product life. The machine is easy to handle by one person thanks to the foldable legs.



ROBUST AND RELIABLE MOTOR
Provides long product life.



EASY SET UP AND TRANSPORT
Thanks to the foldable legs.



VERSATILE
Can plunge and bevel cut at 45° or 90° for maximum versatility.



EFFICIENT SLURRY SEDIMENTATION
The collection tray enables efficient slurry handling for long pump life.

Features Husqvarna TS 350 E

- The high quality water pump greatly extends product life.
- Thanks to the electrical quick connection.
- Thanks to the two rear wheels.
- The solid frame protects the guide rails from external impact.

TECHNICAL SPECIFICATION	
Power	EU 2.2 kW / UK 1.5 kW / US 2.2 kW / JP 1.5 kW / OTHER 2.7 kW / EU 3 hp / UK 2 hp / US 3 hp / JP 2 hp / OTHER 3.6 hp
Motor rpm	2800 rpm
Voltage	EU 230 V / UK 110 V / US 230 V / JP 110 V / OTHER 400 V
Current phase cycle	50 Hz
Engine cooling	Air
Belt	Direct drive
Wet/dry cutting	Wet
Blade shaft RPM	2800 rpm
Spindle diameter	25.4 mm / 1 "
Blade diameter	350 mm / 13.8 inch
Max cutting depth	100 mm / 3.9 inch
Max cutting length	700 mm / 27.6 inch
Water tank volume	40 lit / 10.6 gal.
Electric protection class	IP 55
Weight (excl. cutting equipment)	92 kg / 204.4 lbs
Product size, LxWxH	1120x600x600 mm / 44.09x23.62x23.62 inch
Weight	92 kg / 0 lbs
Weight incl. packaging	110 kg / 0 lbs
Sound power level, guaranteed (LWA)	112 dB(A)
Sound pressure	82 dB(A)
Vibrations rear handle	2.5 m/s ²
Hand arm vibration (Aeq)	2 m/s ²

