



Husqvarna TS 400 F

TS 400 F is an efficient universal masonry saw with high cutting capacity for all kinds of bricks and building blocks.

With this table saw you get a maximum cutting depth of 125 mm in one pass or up to 250 mm by step cutting. You can easily plunge or bevel cut at 45 degrees for maximum versatility. The robust single-piece frame with integrated conveyor rails gives great rigidity and provides longer product life. The machine is easy to handle by one person thanks to the foldable legs.




EASY SET-UP

One person can set up the machine, thanks to the semi-automatic folding legs.



VERSATILE

Can plunge and bevel cut at 45° or 90° for maximum versatility.



EFFICIENT SLURRY SEDIMENTATION

The collection tray enables efficient slurry handling for long pump life.

Features Husqvarna TS 400 F

- Provides long product life.
- Thanks to the four wheels.
- The high quality water pump greatly extends product life.
- The precise height adjustment of the cutter head allows deep step cutting.
- Thanks to the electrical quick connection.
- The solid frame protects the guide rails from external impact.

TECHNICAL SPECIFICATION	
Power	EU 2.2 kW / UK 1.5 kW / US 2.2 kW / JP 1.5 kW / OTHER 2.7 kW / EU 3 hp / UK 2 hp / US 3 hp / JP 2 hp / OTHER 3.6 hp
Motor rpm	2800 rpm
Voltage	EU 230 V / UK 115 V / US 230 V / JP 115 V / OTHER 400 V
Current phase cycle	50 Hz
Engine cooling	Air
Belt	Direct drive
Wet/dry cutting	Wet
Blade shaft RPM	2800 rpm
Spindle diameter	25.4 mm / 1"
Blade diameter	400 mm / 15.8 inch
Max cutting depth	230 mm / 9.1 inch
Max cutting length	700 mm / 27.6 inch
Water tank volume	40 lit / 10.6 gal.
Electric protection class	IP 55
Product size, LxWxH	1120x600x600 mm / 44.5x24.8x26.8 inch
Dimensions uncrated (LxWxH)	1120x600x600 mm / 0x0x0 inch
Weight	96 kg / 211.64 lbs
Weight incl. packaging	125 kg / 277.8 lbs
Sound power level, guaranteed (LWA)	104 dB(A)
Sound pressure	97 dB(A)
Vibrations rear handle	2.5 m/s ²
Hand arm vibration (Aeq)	2 m/s ²

