



KBE 32

Eco magnetic core drill for up to 32 mm

Small and extremely lightweight single-speed economical magnetic core drill with basic functionality for core drilling on the construction site.

Product number: 7 270 94 61 24 1

Details

- > For tough use thanks to the outstanding quality of workmanship and the internal motor cable quide.
- > Extremely durable gearbox design offering an operating time of up to 400 hours for an uncompromising service life.
- > Lightweight with FEIN high-power motor and high torque for all core drilling tasks
 - Excellent price / performance ratio.

- Internal cooling.
- > High magnetic holding force.
- > Feed handwheel can be moved from one side to the other.
- > Good accessibility in cramped operating situations.
- > Personal safety switch.

Price includes

- 1 hand pump
- 1 lashing strap
- 1 contact guard
- 1 case

- 1 bottle holder
- 1 centring pin 100 mm
- 1 socket head wrench 5 mm

Product feature

Feed handwheel can be moved from one side to the other



Application

Workshop jobs

Core drilling in metal with a Ø up to 35 mm

Working overhead

Installation work

★★

**

★ suitable
 ★ well suitable

Technical data

TECHNICAL DATA

Input	1,200 W
Output	770 W
Speed, full load	450 rpm
Speed, no load	700 rpm
Carbide core drill bit max. Ø	32 mm
HSS core drill max. Ø	32 mm
Core drill, drilling depth max.	50 mm
Core drill holder	3/4 in Weldon
Stroke	90 mm
Magnetic holding power	10,000 N
Magnetic foot dimensions	175 x 80 mm
Cable with plug	3 m
Weight according to EPTA	10.80 kg



Application examples











