



## KBE 52-2 M

### Eco magnetic core drill for up to 50 mm

Lightweight and powerful 2-speed Eco magnetic core drill with MT3 tool mounting and basic functionality for core drilling and twist drilling in the workshop and on the construction site.

Product number: 7 270 69 61 24 1

### Details

- > For tough use thanks to outstanding quality of workmanship and swivel-mounted motor cable protective hose.
- > FEIN high-power motor with high torque and large stroke range for core and twist drilling.
- > Uncompromising with regard to service life and work progress coupled with outstanding value for money.
- > Mechanical 2-speed gearbox.
- > MT3 tool mounting.
- > High magnetic holding force.
- > Optimum power-to-weight ratio.
- > Integrated coolant tank.
- > Feed handwheel can be moved from one side to the other with hex hub.
- > Integrated Allen wrench holder.
- > \* Also available with accessories.

### Price includes

- ✓ 1 coolant tank
- ✓ 1 swarf hook
- ✓ 1 contact guard
- ✓ 1 drift key
- ✓ 1 lashing strap
- ✓ 1 centring pin, diameter of 6.35 x 100 mm
- ✓ 2 x 5 and 6 mm hexagon socket wrench
- ✓ 1 case

### Product feature

- ✓ Feed handwheel can be moved from one side to the other



## Application

Core drilling in metal with a  $\varnothing$  up to 35 mm



Core drilling in metal with a  $\varnothing$  up to 50 mm



Twist drills with drill chuck (DIN 338)



Twist drills with MK fitting (DIN 345)



Countersinking



Working overhead



Installation work



Workshop jobs



★ suitable

★★ well suitable



## Technical data

### TECHNICAL DATA

Input	1,200 W
Output	540 W
Speed, full load	260 / 520 rpm
Speed, no load	350 / 680 rpm
Tool Holder	MK 3
Carbide core drill bit max. Ø	50 mm
HSS core drill max. Ø	50 mm
Core drill, drilling depth max.	50(75*) mm
Twist drill max. Ø	23 mm
Core drill holder	3/4 in Weldon
Stroke	135 mm
Total stroke range	260 mm
Magnetic holding power	12,500 N
Magnetic foot dimensions	195 x 90 mm
Cable with plug	3 m
Weight according to EPTA	13.50 kg

## Application examples

