



## AKFH 18-5 AS

### Cordless beveller up to 5 mm

Powerful cordless beveller for perfectly preparing subsequent coatings for flexible jobs in the workshop and on the construction site.

Product number: 7 138 02 62 00 0

## Details

- > For the production of bevels and radii on flat materials, sheet metals and containers, of inner and outer edges, contour shapes and for rounding off holes.
- > High sanding capacity requiring little force and infinitely variable speed setting for different materials.
- > Ergonomic thanks to low weight and compact design.
- > FEIN PowerDrive motor delivers good performance and long service life.
- > Extensive user protection features include soft start, restart protection, jam monitoring and electronic overload protection.
- > COOLPACK 2.0 technology delivers a 135% longer battery life and therefore makes longer operating times possible.
- > State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries.
- > ProCORE Li-Ion battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- > Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- > Ideally equipped for every job. Mobile working with the L-BOXX system.

## Price includes

- ✓ 1 tool incl. 45 milling head (without guide roller, without indexable tips)
- ✓ 1 x copper paste
- ✓ 1 x TX 15 Torx screwdriver
- ✓ 3 x clamping screws SX
- ✓ 1 x 4 mm socket head wrench
- ✓ 1 plastic tool case (L-BOXX 238)

## Product feature

- ✓ Soft start
- ✓ Blockage monitoring
- ✓ Speed preselection
- ✓ Restart protection
- ✓ Electronic overload protection



## Application

Installation work



Bevel length of up to 5 mm at 45°



Workshop jobs



★ suitable  
★★ well suitable

## Technical data

### TECHNICAL DATA

Battery voltage	18 V
Battery compatibility	Li-ion / ProCORE Li-ion
Battery interface	18 V AMPShare
Speed, no load	2,400 - 7,500 rpm
Max. bevel length at 45°	5 mm
Max. bevel height at 45°	3.5 mm
Bevel angle	45°
Radius	1.2 / 2,5 mm
Milling head configuration	3x SX tip
Support plate diameter	98 mm
Weight without storage battery	2.52 kg

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	85 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	96 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	100 dB 3 dB
Vibration value 1 $\alpha_{hv}$ 3-way	3,1 m/s <sup>2</sup>
Vibration value 2 $\alpha_{hv}$ 3-way	4,5 m/s <sup>2</sup>
Uncertainty of measured value K $\alpha$	1,5 m/s <sup>2</sup>

## Application examples

