



## ABSS 18 1.6 E AS Set

### Cordless slitting shears up to 1.6 mm

Compact and curve-compatible nibbler for roof and façade construction. Precise cuts in corrugated sheet metal up to 1.3 mm. Includes battery charger GAL 1880 CV AS, 2x Li ion storage batteries GBA 18V 5.0 Ah AS, additional punch and die set, permanent marker, painter's tape and metre rule.

Product number: 7 130 05 62 00 0

## Details

- > 180 m cutting capacity (in 0.8 mm sheet metal) with one battery charge (5 Ah).
- > Rapid work progress due to excellent view of the cutting line through the open-fronted cutting head.
- > Left and right curve cuts and distortion-free cutting possible with just one continuous chip.
- > QuickIN for rapid toolfree blade changing, with no further adjustment required.
- > Excellent ergonomics and low weight.
- > Cutting blade with excellent tool life.
- > Proven MultiMaster motor with outstanding performance and stability.
- > Compatible with AMPShare/Bosch Professional 18 V batteries.
- > Maximum work progress with AMPShare 18V storage batteries: COOLPACK 1.0 technology ensures a longer storage battery life compared with batteries without COOLPACK technology and therefore makes longer operating periods possible. ECP protects the storage battery against overload, overheating and total discharge.
- > Ideally equipped for every form of use. Mobile working with the L-BOXX system.

## Price includes

- ✓ 1 cutter blade (31308150009) fitted
- ✓ 1 socket head wrench 2,5 mm
- ✓ 1 permanent marker (32133037000)
- ✓ 1 metre rule (18750283000)
- ✓ 1 pair of cutting jaws (31308153014) fitted
- ✓ 1 blade for curves (31308151008)
- ✓ 1 painter's tape (32133038000)
- ✓ 1 tool case (L-Boxx 136)

## Product feature

- ✓ QuickIN
- ✓ Open cutting head
- ✓ Adjustable stroke

Application



Curve cuts



Coil sections



Interior cut-outs



Profile sections



Notches



★ suitable

★★ well suitable

## Technical data

### TECHNICAL DATA

Battery voltage

18 V

Battery compatibility

Li-ion / CORE Li-ions

Battery interface

18 V AMPShare

Strokes

2,200 - 3,500 rpm

Cutting speed

5 - 8 m/min

Steel up to 400 N/mm<sup>2</sup>

1.6 mm

Steel up to 600 N/mm<sup>2</sup>

1.2 mm

Steel up to 800 N/mm<sup>2</sup>

0.8 mm

Non-ferrous metals up to 250 N/mm<sup>2</sup>

2 mm

Cutting width

5 mm

Rad. of smallest curve

48 mm

Immersion Ø

15 mm

### VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA  
Uncertainty of measured value  
KpA

74,3 dB  
3 dB

Sound power level LWA  
Uncertainty of measured value  
KWA

85,3 dB  
3 dB

Sound peak value  
LpCpeak  
Uncertainty of measured value  
KpCpeak

87,6 dB  
3 dB

Vibration value 1  $\alpha_{hv}$  3-  
way  
Uncertainty of measured value  
K $\alpha$

ah 4,6 m/s<sup>2</sup>  
1,5 m/s<sup>2</sup>



Weight without storage  
battery

1.24 kg

Weight without storage  
battery

1.24 kg