



AGSZ 18-280 LBL AS

Cordless die grinder

Dust-resistant and powerful, compact cordless die grinder with large plunge depth for effective cutting, grinding, deburring and milling work.

Product number: 7 123 05 61 00 0



Details

- > Guarantees very long life with the next generation of brushless FEIN PowerDrive motors. Totally closed motor housing protects the motor from aggressive ceramic and mineral dusts.
- Ideal for every application. Optimum speeds, matched to a large number of abrasive materials and other materials using the infinitely variable, electronic speed preselection.
- > Powerful. 30 % more efficiency than comparable universal motors with a rated output of 1 100 W.
- > COOLPACK 2.0 technology delivers a 135% longer battery life and therefore makes longer operating times possible.
- > State-of-the-art cell technology and intelligent battery management deliver 87% more power than with conventional batteries.
- > ProCORE Li-lon battery with high-power cells, charge status indicator and "Electronic Cell Protection" (ECP). ECP protects against overload, overheating and total discharge.
- > Very smooth running and low-vibration working thanks to motor being decoupled from the

- housing and mounted separately and four additional vibration dampers.
- > Extensive user protection features include soft start, restart protection and electronic overload protection.
- > Innovative collets with all-round flange to protect the workpiece and prevent the wrench sliding off during tool changes.
- > Fatigue-free working thanks to narrow grip dimensions, compact design and a well-balanced low weight.
- > Separate motor electronics with dust guard in handle area.
- Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- > Bright working area thanks to integrated LED light.
- > Long, narrow neck allows tool to plunge a long way into workpieces (e.g. grinding inside pipes).
- > Removable rubber collar bearing cover.

Price includes

- 1 collet Ø 6 mm
- Jaw spanner SW17

- Jaw spanner SW13
- 1 plastic tool case (L-BOXX 238)

Product feature

- POWERtronic tacho electronics
- Restart protection
- Electronic overload protection
- Long neck

- Soft start
- Blockage monitoring
- Electronic speed preselection

Application

Cutting





** Roughing-down Grinding Deburring Dividing ★ suitable ★★ well suitable

VALUES

VIBRATION AND SOUND EMISSION

Technical data

TECHNICAL DATA

Battery voltage	18 V	Sound pressure level LpA Uncertainty of measured value KpA	82 dB 3 dB
Battery compatibility	Li-ion / ProCORE Li-ion		
Battery interface	18 V AMPShare	Sound power level LWA Uncertainty of measured value KWA	93 dB 3 dB
Motor	brushless	Sound peak value	96 dB
Speed, no load	9,000 - 28,000 rpm	LpCpeak Uncertainty of measured value KpCpeak	3 dB
Grinding wheel for max.	50 mm	Vibration value 1 αhv 3- way	αh,SG (Ø 50mm) 13,7 m/s²
Collet for max. Ø	8 mm	Vibration value 2 αhv 3-way	αh,SG (Ø 25mm) 6,2 m/s²
Max. cutter diameter	12 mm	Uncertainty of measured value $K\alpha$	1,5 m/s ²
Weight without storage battery	1.77 kg		
Weight without storage battery	1.77 kg		

Application examples





Kompatibel mit AMPShare-/ Bosch Professional 18 V Akkus. | Compatible with AMPShare/Bosch

Professional 18 V batteries. | Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterías AMPShare/Bosch Professional de 18 V. | Compatibile con le batterie AMPShare / Bosch Professional da 18 V.



