

ASB 18 Q AS

2-speed cordless combi drill

With brushless motor and QuickIN interface. Perfectly suited to drilling up to 13 mm in metal, stone and masonry.

Product number: 7 104 07 61 00 0

Details

AMP

- 2-speed solid metal gearbox and switchable striking mechanism for optimum drilling in metal, stone and masonry.
- Enjoy the greatest versatility with the FEIN QuickIN system. Work at speed in metal and timber with just one tool.
- QuickIN solid metal drill chuck (120 Nm) with carbide-tipped clamping jaws and high clamping forces.
- Brushless FEIN PowerDrive motor with 30 % higher efficiency and long service life.
- + Mechanical torque setting.
- + Compact design.
- The AMPShare interface makes almost 50% more screw connections (approx. 1300 screw connections, diameter of 5 x 40 mm in timber) possible per battery charge with the same level of FEIN quality. (ProCORE 4 Ah).

- Bit and belt holder on the side for ergonomic and flexible handling.
- Compatible with all 18 V AMPShare ProCORE batteries and chargers for even more power and flexibility. Also suitable for 18 V Bosch Professional cordless devices.
- Compatible with Bosch Professional 18 V batteries (available since 2008) and AMPShare batteries.
- Maximum work progress with AMPShare 18V ProCORE batteries: COOLPACK 2.0 technology delivers a 135% longer battery life. State-of-theart cell technology and intelligent battery management deliver 87% more power than with conventional batteries. "Electronic Cell Protection" (ECP) protects the battery from overload, overheating and total discharge.
- Ideally equipped for every form of use. Mobile working with the L-BOXX system.

Price includes

- + 1 QuickIN drill chuck (120 Nm)
- + 1 magnetic bit storage

Product feature

- + Removable drill chuck
- + QuickIN accessory interface

- + 1 belt clip
- + 1 tool case (L-Boxx 136)
- + Switchable impact mechanism

Technical data

💮 FEIN

TECHNICAL DATA

18 V

VIBRATION AND SOUND EMISSION VALUES

Battery voltage

Battery compatibility

Battery interface

Motor

Gearbox

Accessory interface

Speed, no load

Impacts

Max. torque (hard/soft)

Torque levels

Drill chuck clamping width

Fastening

Capacity in steel Ø

Capacity in wood Ø

Capacity in stone $\ensuremath{\mathcal{Q}}$

Tapping

Weight without storage battery

Li-ion / ProCORE Li-ion	КрА
18 V AMPShare	Sou Unce KWA
brushless	Sou
2-speed	LpC Unce KpC
QuickIN	
450 / 2,000 rpm	Vibr way ^{Vibra}
7,360 / 32,000 rpm	Unc
60 / 38 Nm	valu
22 + 1	
1.5 - 13 mm	
8 x 300 mm	
13 mm	
50 mm	
13 mm	
M 10	
1.50 kg	

Sound pressure level LpA Uncertainty of measured value KpA

Sound power level LWA Jncertainty of measured value KWA

Sound peak value LpCpeak Uncertainty of measured value KpCpeak

Vibration value 1 αhv 3way Vibration value 2 αhv 3-way

Uncertainty of measured value K α

92,9 dB 3 dB

100,9 dB _{3 dB}

110,0 dB

3 dB

ah,D 1,4 m/s²

ah 0,6 m/s²

1,5 m/s²

Application examples





Kompatibel mit AMPShare-/ Bosch Professional 18 V Akkus. | Compatible with AMPShare/Bosch

Professional 18 V batteries. | Compatible avec les batteries 18 V AMPShare/Bosch Professional. | Compatible con baterías AMPShare/Bosch Professional de 18 V. | Compatibile con le batterie AMPShare / Bosch Professional da 18 V.

