
LF 80
Husqvarna
LF 80

FORWARD PLATE LF 80 L | 420 mm | Honda

LF 80 L is a fast-operating forward plate compactor, ideal for compacting thin to medium layers of granular soils. The unique plate shape and optimised speed enable fast and easy compaction with high production rates. The exclusive, patented low-vibration handle protects you from unhealthy vibration levels and the compact design with foldable handle make transportation and storage easy.

Engine

	FORWARD PLATE LF 80 L | 420 mm | Honda
Motor/engine model	GX160
Engine Power (As rated by the engine manufacturer)	3.6 kW
Power/fuel type	Petrol
Starter	Recoil
Exhaust emissions (CO_2 EU V)	757 g/kWh
Power Source	Petrol

Product data

	FORWARD PLATE LF 80 L | 420 mm | Honda
Compaction application	Soil
Centrifugal force	19 kN
Speed	33 m/min

Dimensions

	FORWARD PLATE LF 80 L | 420 mm | Honda
Plate width	420 mm
Product size length	1,037 mm
Product size width	420 mm
Product size height	1,114 mm
Weight (complete product w/o side packed articles)	84 kg
Packaging length	620 mm
Packaging width	850 mm
Packaging height	840 mm
Article gross weight	93,000 g

Sound and noise

	FORWARD PLATE LF 80 L | 420 mm | Honda
Sound power level, guaranteed (LWA)	105 dB(A)
Sound pressure level at operators ear	91 dB(A)

Vibration

	FORWARD PLATE LF 80 L | 420 mm | Honda

Hand arm vibration (Aeq)	1.2 m/s²
Vibrations left/front handle	6.7 m/s²
Vibrations right/rear handle	1.2 m/s²

© Husqvarna AB (publ). All rights reserved. Prices shown are recommended retail prices.

Cookie policy

Terms of use

Privacy notice

Imprint

Useful links

Contact us

REACH Article 33 Declaration

Status page